



MVOICE 1000 Series USB/Bluetooth Speakerphone

For personal and small group conference

MVOICE 1000 series conference speakerphones are specially designed home based worker, on-line education, and small business conference room, to replace the PCs and mobile phone's speaker and microphone with outstanding audio quality.

- Simply Plug and Play

Easy connect to your PC or laptop via USB, works great with PC based communication softphone i.e Skype, Zoom etc.

- Wireless conference with Bluetooth

Support connection to mobile phone via Bluetooth, turn your mobile phone as a conference gateway anytime anywhere. (MVOICE 1000-B only)

- Integrate with video conference system

Professionally designed to work with video conference systems, provide perfect and cost-effective audio solution to your video conferences.



-Enjoy crisp, clear and rich audio play back

Full band frequency response and advanced CrystalSound audio processing technologies deliver remarkably rich full audio for natural, effortless conversations.

- Ultra-low power consumption

USB charging for 300mAh max, works with ultra low power supply, no worry of drawing too much power from your PC or video conference system

Product Specifications Sheet

Model Name	MVOICE 1000	MVOICE 1000-B
PHOTOS		
Recommended Situations		
Recommended room coverage	10-15m ²	10-15m ²
Conference size	3-5 persons	3-5 persons
Microphone		
Sound pick up range	3m	3m
Microphone response frequency	30Hz-16KHz	30Hz-16KHz
Built-in Mic	3	3
Expandable Mic	N/A	N/A
Speaker		
Max output(dB)	83dB	83dB
Speaker response frequency	30Hz-16KHz	30Hz-16KHz
Audio		
Full Duplex	√	√
Dynamic Noise Reduction (DNR)	√	√
Automatic Gain Control (AGC)	√	√
Connectivity		
USB cable	√	√
Bluetooth connectivity	N/A	BT Version:3.0 BT profile:HSP / HFP / A2DP Wireless output:Class 2 Max.communication distance:10m(32.8ft)
Package		
Unit Dimensions	Φ140 x 32mm	Φ140 x 32mm
Package Dimensions	245x170x50mm	245x170x50mm
Weight	0.5kg	0.5kg
Accessories	Protective Travel Case USB cable,English User's Manual	Protective Travel Case USB cable, English User's Manual
Environments		
System requirements	windows XP windows Vista windows 7/8/10	windows XP windows Vista windows 7/8/10
Power Input	USB:5 V DC @ 300 mA Maximum	USB:5 V DC @ 300 mA Maximum
Operating temperature	5°C—40°C	5°C—40°C
Storage temperature	-30°C—55°C	-30°C—55°C
Rechargeable battery	N/A	√ Over 4-hours talk time
Compliance	FCC / CE / RoHS	FCC / CE / RoHS/BQB